

# बागमती प्रदेश सरकार कृषि तथा पशुपन्छी विकास मन्त्रालय कृषि विकास निर्देशनालय

# कृषि विकास कार्यालय, सिन्धुली

सिन्धुलीमाढी, नेपाल

सचना नं १०/२०८२/०८३

प्रथम पटक प्रकाशित मितिः २०८२/०९/०६

कृषि विकास कार्यालको सिन्धुलीको आ.व. २०८२/८३ को वार्षिक स्वीकृत कार्यक्रम अनुसार विभिन्न कृषि प्रवर्द्धन/ कृषि विकास कार्यक्रम संचालनार्थमा कृषकहरुको माग तथा स्वीकृत वजेको परिधि भित्र रही कृषि यन्त्र/औजार/ उपकरणहरू अनुदानमा उपलब्ध गराउने प्रयोजनका लागि कृषि यन्त्र/औजार/उपकरणहरू न्युतम दरभाउमा आपुर्ति गर्न इच्छुक न्युनतम योग्यता पुगेका आधिकारिक उत्पादक/बिक्रेता/फर्महले यो सूचना प्रकाशित भएको मितिले १४ औं दिन (२०८२/०९/२०) सम्ममा कार्यालय समय भित्र उल्लेखित कागजातहरु सहित सिलबन्दी दरभाउ प्रस्ताव पेश गर्नुहुन यो सूचना प्रकाशन गरिएको छ । कृषि/औजार/उपकरणहरूको प्राविधिक स्पेशिफिकेसन र सिलवन्दी दरभाउ प्रस्ताव फाराम यस कार्यालय तथा कार्यालयको वेवसाईट https:// sindhuli.akc.gov.np बाट डाउनलोड गरी प्राप्त गर्न सिकने छ ।

शिलबन्दी दरभाउ प्रस्ताव दर्ता गर्ने निकायः कृषि विकास कार्यालय, सिन्धुली

## आवश्यक कागजात तथा शर्तहरुः

- १.आधिकारिक सहिछाप सहितको निवेदन.
- २.आधिकारिक सहिछाप सहितको निर्धारित ढाँचा वमोजिमको पूर्ण रुपमा भरिएको शिलवन्दी दरभाउ प्रस्ताव फाराम,
- ३.फर्म/संस्था/कम्पनी दर्ता तथा नविकरणको प्रमाण पत्र, मूल्य अभिवृद्धि कर (भ्याट)/ प्यान दर्ता प्रमाण पत्रको प्रतिलिपि,
- ४.कम्पनीको हकमा कम्पनी रजिष्टार कार्यालयवाट गरिने कम्पनी अध्यावधिक भएको पत्र,
- ५.आ.व. २०८१/८२ को कर चुक्ता तथा लेखा परिक्षणको प्रमाणित प्रतिलिपि, नेपाली नागरिकताको प्रतिलिपी ।
- ६.सामाग्रीहरूको उत्पादक कम्पनिहरूको आधिकारिक विकेता वा Authorized agent/डिलरसिप रहेको प्रमाण पत्र,
- ७.आपुर्तिकर्ताले आपुर्ति गर्ने खोजेको कृषि यन्त्र/औजार/उपकरणहरूको मोडल र ब्रान्डहरूको आधिकारिक टेप्ट रिपोर्टको प्रमाणित प्रतिलिपि,
- प्र.आपुर्ति गर्न सिकिने कृषि यन्त्र/औजार/उपकरणहरुको स्पेशिफिकेसन, ब्रान्ड, मोडेल, उत्पादक कम्पनी र देश खुल्ने क्याटलग, लिफलेट वा ब्रोसर अनिवार्य रुपमा पेश गर्नुपर्ने छ ।

थप जानकारीको लागि यस कार्यालयको सूचना पाटी, फेसबुक पेज, फोन नं ०४७-५२१०४२ तथा यस कार्यालयको वेवसाईट sindhuli.akc.gov.np बाट प्राप्त गर्न सिकेनेछ ।

	Manual Operated Push Seeder			
	Items	Required Specification	Offered Specification	
1	General	Manual operated push seeder, suitable for planting maize, giving smooth economic performance.		
2	Number of rows	single row		
3	Seed Metering Mechanism	Plate type (seed plate with specific holes for maize seed)		
4	Seed Spacing	Adujustable; typically 15 cm to 30 cm		
5	Depth	2.5 cm -3.5 cm		
6	Hopper Capacity	2-5 kg		
7	Wheel Type	Ground wheel-driven (for metering); rubber wheels		
8	Field capacity	not less than 0.1ha/hr		
	Total Price (Nrs.)			
	Total price in word			

A.



अधिकंपस्पर अव्या)

S.N.	Name of implement with description	Required specification	Offered Specification by suppiler with remark
A	Power Weeder		
1	Brand/model	Make: 2025 or latest model; Brand; Model: any	
2	General	A power weeder is used to remove weeds and till the soil efficiently, reducing manual effort and improving crop productivity.	
3	Engine	Single cylinder, four-stroke, Petrol engine, Maximum power not less than 2 kW at rated speed.	
4	Starting type	Recoil/ Electrical starter	
5	Transmission system	Gear drive	
6	Displacement(ml(cu.in))	not less than 50 CC	
7	Fuel tank capacity	not less than 1 L	
8	Blades	minimum 24	
9	Tilling Depth	100mm or above	
10	Tilling width	550 mm or above	
	Total Price (Nrs.)		
	Total price in word		

Jef.



अधिकृतस्तर नवौं) (अधिकृतस्तर नवौं)

		cation For Farm Machinery and Equipments	
S.N.	Name of implement with description	Required specification	Remarks
A	Combined mill		
1	Make and model	any	Make: 2025 or leatest model; Brand; Model: any
	General	Application in both milling of ceareals such as rice, wheat, millet and paddy, Gross wt not less than 70 kg.	
2	Power Source	not less than 2KW	
3	Motor	100% copper	
4	voltage and frequency of motor	220volt,50Hz	
5	Seive size	at least 100*749mm	
6	Seive Diameter	aperture: 1.2	
7		Rice mill: at least 80 kg/hr	
8	Capacity	Grain grinder: at least 130kg/hr	
9	Roller Speed	Rice mill-at least 1500rev/min	
10			
11	Roller Diameter: rice mill	40mm	
12	Types	Disc/Hammer types	
13	accessories	Electric wire along with Suitable MCB with switch	
H I	Total Price (Nrs.)(A)		





S.N.	Name of implement with description	Required specification	Remarks
	Minitiller		
	Brand/ Model	Any	Make: 2025 or latest model; Brand; Model: any
	Tilling Depth	minimum 150	
	Tiller Breadth	minimum 1150	
	Gearshif Speed	2 Fwd and 1 Rev Gear	
	Blades Type	4 pcs 5 groups(40 pcs)	
	Driving model	gear drive	
	Wheel	5.00-12	
	Engine Model	186F	
	Engine type	Diesel	
	Displacement [ml(cu.in)]	not less than 418 CC	
	Engine speed(rpm)	3600	
	Compression ratio	20:01	
	Fuel tank volume [L (gal.)]	not less than 5 L	
	Engine Oil Capacity	not less thna 2L	
	Gear Oil Capacity	not less than 2L	
	Clutch	Wet Friction Plate	
	Starting system	Recoil (Manual) Start	
	Color	Standard	
	Lube brand/Type	SAE10W-30	
	Packing	Wooden box	
	Certificate	ISO	
	Gross Weight (Including Wooden Box)	185	
	Total Price (Nrs.)		
	Total price in word		
	AND DESCRIPTION OF THE PROPERTY OF THE PROPERT		



भणे विश्व अधिक्तस्तर नवीं) (अधिक्तस्तर नवीं)

		Technical Specification	
S.N.	Name of implement with description	Specification required	offered specification
A	Corn sheller		
1	Make and model	any	
2	Power	0.48 kw	
3	Motor	copper Coil 100%	
4	Capacity	600-700kg/hr	
6	Gross wt	minimum 18kg	
7	Tube	Single	
	Price in word (NRs)		
В	Corn sheller	•	
1	Make and model	any	
2	Power .	at least 0.75 kw	
3	Motor	copper Coil 100%	
4	Capacity	900-1200 kg/hr	
6	Rotor Diameter	around 590mm	
7	Tube	double	
	Price in word (NRs)		

sof.



अणुप अशिकारी प्रमुख (अधिकृतस्तर नवीं)

APA IN	Technical Specification of rotavator with bed maker			
S.N.	Name of implement with description	Required specification	Offered Specification by suppiler	
1	General	Rotavator is a tractor-drawn implement which is mainly used for seed bed preparation, weight not less than 450kg	make: 2025 or latest, model:	
2	matching tractor power	Greater than 45HP tractor PTO.		
3	Overall working width	5/6 feet		
4	Gear box	single/ multispeed  All speed archived diffrient number gear should be provided.		
6	transmission system	gear box transmission system		
7	PTO shaft	around 14" Pipe with 6/21 Spline Couplers		
8	Blade type	j,c and s type		
9	number of blade	at least 42		
	Total Price			
	Total price in word			



शनुप अधिकारी



Technical Specification of paddy thresher

S.N.	Name of Implements With Description	Technical Specification	Specification of proposed item
	Paddy Thresher		
1	make, model, brand	make: 2025 or latest	
2	General	It is used for threshing of paddy, maize, wheat, sorghum, barley.  Provided at least 3 types of grain sieve.	953
3	Power requirement(hp/kW)	above 40 HP, tractor pto	
4	Working efficiency	>-1200kg/hr	
5	Threshing efficiency	>-97%	
6	Overall grain loss	<-2.5%	
7	Broken grain loss	<-0.8%	
8	Blown grain loss	<-1.5%	
9	Crop feeding	direct hopper type(Feeding chute, manually)	
10	Type of cylinder	Spike tooth	
11	Cylinder size, tip diameter x length(m m)	approx.770 x 1500	
12	No of sieves	3	
13	No. of blower	one/double/triple	
14	No. of spike	around 75	
15	Cleaning fan	at least1 aspiratory fan for grain clean and 1 centrigugal fan for dust clean	
16	Weight(approx.)	1450-1550kg	
17	Strandard accessories	PTO shaft,tool box,greas gun	
18	Main shaft diameter	not less than 60mm	
19	No. of transmission joint	not less than 3	
	Total price		
	Total price in words		1 Milan

अशिक्तस्तर नवीं)



<b>/</b>	Digital Weighing Balance				
	Items	Required Specification	Offered Specification		
1	General	Digital Weighing Balance, suitable for weighing agricultural products, giving smooth economic performance.			
2	Material	Stainless Steel (non-corrosive)			
3	. Output	Bright LED Digital Display			
4	Weighing Capacity	100 kg			
5	Instructions	All signs and instruction in an Digital balance shall be in English/Nepali			
6	Others	Battery backup, auto zero tracking			
	Total Price (Nrs.)				
	Total price in word				



SN	Items/Description	Specification	Specification of proposed item
		Jab Planter	
1	General	Its main application is for planting seeds, and in the case of a double-barrel type, applying fertilizer simultaneously	
2	Model	Any	
3	Type	Double	
4	Operation	Manually	
5	Model	Seed and fertilizer	
6	Seeding	Adjustable 1-3 seeds	
7	Gross wt	2.5 kg	
8	Application	Maize, bean etc	
	Total Price (Nrs.)		
	Total price in word		



S.N.	Name of implement with description	Required specification	Offered Specification by suppiler with remark
A	Minitiller		
1	Brand/model	Make: 2025 or latest model; Brand; Model: any	
2	General	General purpose minitiller for dry and wet tillage, with standard desgin having gross vehicle weight not less than 80kg	
3	Engine	Single cylinder, Four stroke, Forced air cooled system, Oil batch type filler, Petrol engine, Maximum power not less than 4KW at rated speed.	
4	Starting type	Recoil/ Electrical starter	
5	Transmission system	Gear drive( 1- Reverse, 2- Forward( both high and low) number of gears.	
6	Displacement(ml(cu.in))	not less than 208CC	
7	Fuel tank capacity	not less than 2.5 L	
8	Blades	minimum 24	
9	Tilling Depth	100mm or above	
10	Tilling width	750mm or above	
	Total Price (Nrs.)		
	Total price in word		
В	Minitiller		
1	Brand/model	any	
2	General	General purpose minitiller for dry and wet tillage, with standard desgin having gross vehicle weight not less than 120kg	
3	Engine	Single cylinder, Four stroke, Forced air cooled system, Oil batch type filler, Diesel Engine, Maximum power not less than 4KW at rated speed.	
4	Starting type	Recoil/ Electrical starter	
5	Transmission system	Gear drive( 1- Reverse, 2- Forward( both high and low) number of gears.	
6	Displacement(ml(cu.in))	not less than 296CC	
7	Tilling Depth	100mm or above	
8	Tilling width	750mm or above	
9	Fuel tank capacity	minimum 3.5 litres	
10	Blades	minimum 32 pieces	
11	Tyre	Standard size(4-8)	
12	Colour	Standard	
	Total Price (Nrs.)	AR ON	n Allmean
SE	Scanned with Car		अण्य अधिसारी


S.N. Name of implement with description		Name of implement with description Required specification	Offered Specification by suppiler with remark
A	Bed Marker Minitiller		
1	Brand/model	Make: 2025 or latest model; Brand; Model: any	
2	General	General purpose minitiller for dry and wet tillage and making bed,rear tilling and front traveling with standard desgin having gross vehicle weight not less than 125kg	
3	Bed making mechanism	ditching and furrow blades	
4	Engine .	Single cylinder, Four stroke, Forced air cooled system, Oil batch type filler, Diesel Engine, Maximum power not less than 4KW at rated speed.	
5	Starting type	Recoil/ Electrical starter	
6	Transmission system	Gear drive(1- Reverse, 2- Forward(both high and low) number of gears.	
7	Displacement(ml(cu.in))	not less than 296CC	
8	Tilling Depth	100mm or above	
9	Tilling width	750mm or above	
10	Fuel tank capacity	minimum 3.5 litres	
11	Blades	minimum 32 pieces	
12	Туге	Standard size(4-8)	
13	Frame	MS material	
14	Colour	Standard	
	Total Price (Nrs.)		
	Total price in word		

Arf.



अनुख प्रमुख

(अधियः स्तर नवीं)



S.N.	Name of implement with description	Required specification	Offered Specification by suppiler with remark
A	Minitiller		
112-1	Brand/model	Make: 2025 or latest model; Brand; Model: any	
2	General	General purpose minitiller for dry and wet tillage, with standard desgin having gross vehicle weight not less than 95 kg	
3	Engine	Single cylinder, Four stroke, Forced air cooled system, Oil batch type filler, Diesel Engine, Maximum power not less than 4KW	
4	Starting type	Manual/Recoil	
5	Transmission system	Gear drive(1-Reverse, 2-Forward(both high and low) number of gears.	
6	Displacement(ml(cu.in))	not less than 247CC	
7	Tilling Depth	100mm or above	
8	Tilling width	750mm or above	
9	Fuel tank capacity	minimum 2.5 litres	
10	Blades	minimum 24 pieces	
11	Tyre	Standard size(4-8)	
12	Colour	Standard .	•
	Total Price (Nrs.)		
- 41	Total price in word		



अनुप अधिकारी



Technical Specification of Bag Closer Sewing Machine

S.N.	Name of Implements With Description	Technical Specification	Specification of proposed item
	Bag Closer Sewing Machine		
1	make, model, brand	make: 2025 or latest	
2	General	A portable/handheld industrial bag closing sewing machine designed to securely close filled bags (paper, jute, burlap, PP/PE, woven plastic, HDPE, cotton, hessian, etc.). Suitable for agricultural post-harvest operations, warehouses, packaging lines, and small to medium industrial use	
3	Machine Type	Portable industrial bag closer / bag sealing sewing machine	
4	Operation	Electric powered portable/handheld	
5	Stitch Type	Single thread chain stitch / shall have an optional double thread chain stitch	
6	Maximum Material Thickness	upto 8-10 mm (multi-layer bags)	
7	Power Rating	190-210 W	
8	Voltage	110/220-240 V AC (single phase)	
9	Motor speed/RPM	8000-10000 RPM for sewing head	
10	Body	Cast/forged metal housing for durability	
11	Approx. weight	2.8-7 kg	
12	Bags per hour	at least 150 bags/hr	
13	Accessories	Spring balancer or shoulder strap for ease of operation Spare needles, thread stand, lubricating oil bottle	5#8
14	Warranty	Suppliers shall provide at least 12 months for parts and service.	
-	Total price		
400	Total price in words		





	Technical Specifica	tion For Farm Machinery and Equ	ipments
S.N.	Name of implement with description	Required specification	Offered Specification by suppiler
Α	Electric Winnower		
1	Туре	Electric Grain Winnower Machine	
2	Size	at least 24"	
3	Power	at least (0.24KW)	
4	Volatge	220v/50hz/single phase	
5	Gross weight	around 25kg	
6	Capacity	at least 1000kg/hr	
	Total Price (Nrs.)		
	Total price in word		



अधिकृतस्तर नवौं)



	Technical Specification For Farm Machinery and Equipments				
S.N.	Name of implement with description	Required specification	Offered Specification by suppiler		
A	Power sprayer				
1	Make, model, beand	any			
2	Rated power	at least 4.84±0.2 KW			
3	vertical range	at least 13m			
4	engine type	4 stocke-petrol			
5	suction volume	at least 20 ltr/min			
6	Delivery pipe	at least 2*100 meter			
	Total Price (Nrs.)				
	Total price in word				



अनुप अधिकारी

#### Technical Specification For Farm Machinery and Equipments

S.N.	Name of implement with description	Required specification	Offered Specifcation
A	Battery cum manaul Sprayer (2in1)		
1	tank capacity	At least 16 litter -	
2	Motor	12V motor powered diaphragm pump of speed 3300rpm, 12V,8AHr rechargeable.	
3	working pressure	at least 0.4 Mpa	
4	Charger input:	100-240V AC,50Hz,	
5	charge output	12V DC 1.5A	
6	Spray flow	not less than 2100ml/min,	
7	time of full charge	5 to 8hr	
8	Gross weight	at least 2.6kg	
1	Total Price (Nrs.)		
	Total price in word		



अनुप अधिकारी

specification of Drip irrigation with fertigation unit

S.N	Description	Design of the second	Required Specification	offered specification	offered rate with vat
1	Head unit				
	Screen filter		Cylindrical shape Screen filter with external thread of inlet and outlet 75mm, 150 mesh with capacity not less than 40m <sup>3</sup> /hrs  A 50 mm (2-inch) screen filter typically has a flow		
			capacity of about 10-25 m³/hr and uses an 80-150		
a			mesh stainless steel or plastic screen		
b	Hydrocyclone Filter		size of 65mm, pressure not less than 1.5kgf/cm2, 32-40m3/hr		
С	VENTURI SYSTEM with manifold		used for Fertilizer & Chemical injection through drip irrigation system of size 2", should have amount of fertilizer injected amount reading scale.		
d	Control valve 50 MM				
е	Flush valve 50 MM				
f	Elbow 50 MM				
g	Equal tee 50 MM	lat.			
h	MTA 50 MM				
i	FTA 50 MM				
j	Check Valve (50 MM)				
k	PVC L-75MM				
1	T-63MM				
m	PVC Reducer 75*63				
n	PVC L-63MM				
0	UPVC MTA, FTA				
2	MAIN LINE / SUB MAIN LINE				
			VACUUM RELIFE VALVE 63/ end cap with lock and unlock machanism		
10			16 mm plain pipe		
С	ONLINE DRIP PIPE 16MM		30/30 cm spacing of online drip pipe of discharge not less than 11/hr		
d	GROMMET TECH-UP				
c	END CAP				

CS

Scanned with CamScar

TO GO TO LOT OF THE PARTY OF TH

Anuf Milcan
310JU 318EIDIEL
THE

(अधिकृतस्तर् नवौं)

### Technical Specification of self propelled reaper

S.N	Description	Required Specifications	Offered Specification by suppiler
Α	Self propeller reaper		Make: 2025 or leatest model; Brand; Model: any
1	general	it is used for harvesting of paddy in wet and dry field. Having a self engine for its operation.	
2	engine model	Any	
3	Engine power	not less than 4 ± 0.2KW	
4	Engine Type	4-Stroke, Single Cylinder, Air Cooled, Disel Engine, gear/belt T.S.	
5	Engine Speed	minimum 2600 RPM	
6	Fuel Tank Capacity	minimum 3.5L	
7	Fuel consumption	550-700 ml/h	
8	Starting System	Electric/Manual Starting (Recoil Type)	
9	Cutting Height	minimum 40 mm	
10	Cutting Width	minimum 1000mm	
11	Weight	minimum200kg	
	Total Price (Nrs.)		
	Total price in word		



अधिकृतस्तर नवीं)



	Tec	hnical Specification of farm equipment					
	Steam Boiler Machine						
	Items	Required Specification	Offered specification				
1	General	Steam Boiler Machine primarily used for generating steam needed for sterilization of substrates like straw, sawdust, or compost.					
2	Boiler type	vertical Steam Boiler					
3	Heating Method	Wood-fired					
4	Chimney Height	not less than 8 feet					
5	Water Capacity	not less than 200 ltr					
6	Safety Devices	Pressure Relief Valve, Safety Valve					
7	Instrument	Supply of pressure reading gauge					
8	Accessories	The boiler shall be supplied with steam outlet pipe, condensate outlet, blow-down/drain outlet, and all required valves, flanges, and fittings for safe and efficient steam distribution.					
11.7	Total Price (Nrs.)						
	Total price in word						



अधिकृतस्तर नवीं)

S.N	Description	Required Specification	unit	offered rate with vat
		Protected agriculture related		
	UV plastic	UV Plastic with Minimum 200 Micron is used to Cover the Roof of Iron made  Tunnel	sqm	
1		UV Plastic with Minimum 100 Micron is used to Cover the Roof of bambo Tunnel	sqm	
		UV Plastic with a Minimum 90 GSM is used to cover the Roof of the Tunnel	sqm	
		40 Mesh UV Insect is used for the Sides of the Tunnel (40 Mesh UV insect net_80		
2	Insect Net	GSM)	sqm	
3	Locking Profiles	GI Profile and Zinc Coated Spring is used to Lock the Plastic/ Insect Net.	rm	
4	Shade Net	UV stabilized 50 % shade	sqm	

Agricultural Engineer NEC NO: 83747

अधिकृतस्तर नवीं) (अधिकृतस्तर नवीं)